



Product parameters

Product Description	BKZJ1003D is an unmanaged commercial Ethernet switch module. It supports three 10/100M RJ45 Ethernet ports. DC 9-48V power input. It is suitable for embedded development integration in different scenarios.
Ports	3*10/100 RJ45 ports
POE port	Support customization: 1POE IN 2 POE OUT 12--24 V POWER 4/5V+ 7/8 V-
Technology	Standard: IEEE802.3、IEEE802.3u、IEEE802.3x Flow control: IEEE802.3x. Back Pressure
Interface	10Base-T/100Base-TX self-adapting
Transmission Distance	Twisted pair: 100M (Standard CAT5/CAT5e cable)
Exchange Attribute	100Mbps forwarding speed: 148810pps Transmission method: Store and forward System exchange broadband: 1.6G
Power Supply	Input voltage: 12V DC (Support customization 24VDC)
Consumption	No load: 0.3W@12VDC
Working Environment	Operating temperature: -10 ~ +65°C storage temperature: -40 ~ +85°C humidity: 10%~95 % (No condensation)
Product Structure	Weight: XXXKG Dimension:61*41*17MM(Length X width X height)
Product application	This product is an embedded integrated module for conference room systems, education systems, security systems, industrial computers, robots, gateways, and so on.