


General Performance IEC Inlet Filter



- Rated currents up to 20 A
- Excellent performance/size ratio
- Optional medical versions (B type) according to IEC/EN 60601-1
- Snap-in versions (S and S1 type)
- Hot inlet versions (HI type)
- Optional overvoltage protection (Z type)



Performance indicators

Attenuation performance



Rated current [A]



Approvals & Compliances



(CQC except HI-types)

The FN 9222 IEC inlet filter combines an IEC inlet and mains filter with excellent filter attenuation in a small form factor. Choosing the FN 9222 product line brings you the rapid availability of a standard filter associated with the necessary safety acceptances. Standard IEC connector filters are a practical solution helping you to pass EMI system approval in a short time. A wide selection on amperage ratings, output connections, mounting possibilities and filters for medical applications are designed to offer you the desired solution.

Features and Benefits

- Exceptional conducted attenuation performance, based on chokes with high saturation resistance and excellent thermal behavior
- Rear/front or snap-in mounting
- Wide mounting flanges available
- FN 9222 B versions comply with the requirements of 1MOP acc. to IEC/EN 60601-1 for creepage and clearance, leakage current and high potential testing
- 12 and 15 A types with hot inlet available
- Optional surge pulse protection
- Different output connections offering maximum flexibility for assembly
- Custom-specific versions are available on request

Family Technical Specifications

Maximum continuous operating voltage	250 VAC, 50/60 Hz
Nominal operating voltage	230 VAC
High potential test voltage	P → N 250 VAC for 2 sec (all Z types) P → PE 2000 VAC for 2 sec (standard types) P → PE 2500 VAC for 2 sec (B types) P → N 1000 VAC for 2 sec (1 to 10 A types, not Z types) P → N 1100 VDC for 2 sec (16 and 20 A types, not Z types) P → N 1100 VDC for 2 sec (16 and 20 A types, not Z types)
Rated currents	1 to 20 A @ 50°C
Temperature range (operation and storage)	-25°C to +85°C (25/85/21)
Protection category	IP 40 according to IEC 60529
Flammability corresponding to	Plastic Material: UL 94 V-0 Laces for -07 version: UL 94 VW-1
Approvals by rated current	1 to 10 A (ENEC, CQC) 16 A (ENEC, CQC) for 16 and 20 A types 1 to 20 A (UL, CSA)
Design corresponding to	UL 1283, CSA 22.2 No. 8 1986, IEC/EN 60939 (X to XX A, not Z types)
MTBF (Mil-HB-217F)	≤15 A: >3,040,000 h @ 50°C/230 V ≥16 A: >2,256,000 h @ 50°C/230 V
Operating frequency	DC to 400 Hz

Typical Applications

- Portable electrical and electronic equipment
- Small to medium-sized machines and household equipment
- Single-phase power supplies, switch-mode power supplies
- Test and measurement equipment
- Medical equipment
- Rack mounting equipment

Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance		Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1		Cx1 (μF)	Cy1 (μF)			
FN9222-10-06	10	0.31	0.225		0.1	2.2			
FN9222-10-07	10	0.31	0.225		0.1	2.2			
FN9222-1-06	1	0.31	12		0.1	2.2			
FN9222-1-07	1	0.31	12		0.1	2.2			
FN9222-12-06	12	0.31	0.11		0.1	2.2			
FN9222-12-06HI	12	0.31	0.11		0.1	2.2			
FN9222-12-07	12	0.31	0.11		0.1	2.2			
FN9222-12-07HI	12	0.31	0.11		0.1	2.2			
FN9222-15-06	15	0.31	0.075		0.1	2.2			
FN9222-15-06HI	15	0.31	0.075		0.1	2.2			
FN9222-15-07	15	0.31	0.075		0.1	2.2			
FN9222-15-07HI	15	0.31	0.075		0.1	2.2			
FN9222-16-06	16	0.37	0.54		0.33	2.2			
FN9222-20-06	20	0.37	0.4		0.33	2.2			
FN9222-3-06	3	0.31	2.5		0.1	2.2			
FN9222-3-07	3	0.31	2.5		0.1	2.2			
FN9222-6-06	6	0.31	0.78		0.1	2.2			
FN9222-6-07	6	0.31	0.78		0.1	2.2			
FN9222-8-06	8	0.31	0.5		0.1	2.2			
FN9222A-8-06	8	0.07	0.5		0.1	2.2			
FN9222B-10-06	10	0	0.225		0.1	2.2	1000		
FN9222B-10-07	10	0	0.225		0.1	2.2	1000		
FN9222B-1-06	1	0	12		0.1	2.2	1000		
FN9222B-1-07	1	0	12		0.1	2.2	1000		
FN9222B-12-06	12	0	0.11		0.1	2.2	1000		

Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance		Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1		Cx1 (μF)	Cy1 (μF)			
FN9222B-12-06HI	12	0	0.11		0.1	2.2	1000		
FN9222B-12-07	12	0	0.11		0.1	2.2	1000		
FN9222B-12-07HI	12	0	0.11		0.1	2.2	1000		
FN9222B-15-06	15	0	0.075		0.1	2.2	1000		
FN9222B-15-06HI	15	0	0.075		0.1	2.2	1000		
FN9222B-15-07	15	0	0.075		0.1	2.2	1000		
FN9222B-15-07HI	15	0	0.075		0.1	2.2	1000		
FN9222B-3-06	3	0	2.5		0.1	2.2	1000		
FN9222B-3-07	3	0	2.5		0.1	2.2	1000		
FN9222B-6-06	6	0	0.78		0.1	2.2	1000		
FN9222B-6-07	6	0	0.78		0.1	2.2	1000		
FN9222R-10-06	10	0.31	0.225		0.1	2.2	1000		
FN9222R-10-07	10	0.31	0.225		0.1	2.2	1000		
FN9222R-1-06	1	0.31	12		0.1	2.2	1000		
FN9222R-1-07	1	0.31	12		0.1	2.2	1000		
FN9222R-12-06	12	0.31	0.11		0.1	2.2	1000		
FN9222R-12-06HI	12	0.31	0.11		0.1	2.2	1000		
FN9222R-12-07	12	0.31	0.11		0.1	2.2	1000		
FN9222R-12-07HI	12	0.31	0.11		0.1	2.2	1000		
FN9222R-15-06	15	0.31	0.075		0.1	2.2	1000		
FN9222R-15-06HI	15	0.31	0.075		0.1	2.2	1000		
FN9222R-15-07	15	0.31	0.075		0.1	2.2	1000		
FN9222R-15-07HI	15	0.31	0.075		0.1	2.2	1000		
FN9222R-16-06	1	0.31	0.54		0.33	2.2	1000		
FN9222R-20-06	20	0.31	0.4		0.33	2.2	1000		



















































Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance		Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1		Cx1 (μF)	Cy1 (μF)			
FN9222R-3-06	3	0.31	2.5		0.1	2.2	1000		
FN9222R-3-07	3	0.31	2.5		0.1	2.2	1000		
FN9222R-6-06	6	0.31	0.78		0.1	2.2	1000		
FN9222R-6-07	6	0.31	0.78		0.1	2.2	1000		
FN9222R-8-06	8	0.31	0.11		0.1	2.2	1000		
FN9222RA-20-06	20	0.07	0.54						
FN9222RA-6-06	6	0.07	0.4						
FN9222RB-16-06	16	0	0.54		0.33		1000		
FN9222RB-20-06	20	0	0.4		0.33		1000		
FN9222S-10-06	10	0.31	0.225		0.1	2.2			
FN9222S-10-07	10	0.31	0.225		0.1	2.2			
FN9222S-1-06	1	0.31	12		0.1	2.2			
FN9222S-1-06-20	1	0.31	12		0.1	2.2			
FN9222S-1-07	1	0.31	12		0.1	2.2			
FN9222S1-10-06	1	0.31	0.225		0.1	2.2			
FN9222S1-10-07	10	0.31	0.225		0.1	2.2			
FN9222S1-1-06	1	0.31	12		0.1	2.2			
FN9222S1-1-07	1	0.31	12		0.1	2.2			
FN9222S1-12-06	12	0.31	0.11		0.1	2.2			
FN9222S1-12-07	12	0.31	0.11		0.1	2.2			
FN9222S1-15-06	15	0.31	0.075		0.1	2.2			
FN9222S1-15-07	15	0.31	0.075		0.1	2.2			
FN9222S-12-06	12	0.31	0.11		0.1	2.2			
FN9222S-12-07	12	0.31	0.11		0.1	2.2			
FN9222S1-3-06	3	0.31	2.5		0.1	2.2			






























Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance		Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1		Cx1 (μF)	Cy1 (μF)			
FN9222S1-3-07	3	0.31	2.5		0.1	2.2			
FN9222S-15-06	15	0.31	0.075		0.1	2.2			
FN9222S-15-07	15	0.31	0.075		0.1	2.2			
FN9222S1-6-06	6	0.31	0.78		0.1	2.2			
FN9222S1-6-07	6	0.31	0.078		0.1	2.2			
FN9222S1-8-06	8	0.31	0.5		0.1	2.2			
FN9222S1B-10-06	10	0	0.225		0.1		1000		
FN9222S1B-10-07	10	0	0.225		0.1		1000		
FN9222S1B-1-06	1	0	12		0.1		1000		
FN9222S1B-1-07	1	0	12		0.1		1000		
FN9222S1B-12-06	12	0	0.11		0.1		1000		
FN9222S1B-12-07	12	0	0.11		0.1		1000		
FN9222S1B-15-06	15	0	0.075		0.1		1000		
FN9222S1B-15-07	15	0	0.075		0.1		1000		
FN9222S1B-3-06	3	0	2.5		0.1		1000		
FN9222S1B-3-07	3	0	2.5		0.1		1000		
FN9222S1B-6-06	6	0	0.78		0.1		1000		
FN9222S1B-6-07	6	0	0.78		0.1		1000		
FN9222S1B-8-06	8	0	0.5		0.1		1000		
FN9222S1R-10-06	10	0.31	0.225		0.1	2.2	1000		
FN9222S1R-10-07	10	0.31	0.225		0.1	2.2	1000		
FN9222S1R-1-06	1	0.31	12		0.1	2.2	1000		
FN9222S1R-1-07	1	0.31	12		0.1	2.2	1000		
FN9222S1R-12-06	12	0.31	0.11		0.1	2.2	1000		
FN9222S1R-12-07	12	0.31	0.11		0.1	2.2	1000		







Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance		Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1		Cx1 (μF)	Cy1 (μF)			
FN9222S1R-15-06	15	0.31	0.075		0.1	2.2	1000		
FN9222S1R-15-07	15	0.31	0.075		0.1	2.2	1000		
FN9222S1R-3-06	3	0.31	2.5		0.1	2.2	1000		
FN9222S1R-3-07	3	0.31	2.5		0.1	2.2	1000		
FN9222S1R-6-06	6	0.31	0.78		0.1	2.2	1000		
FN9222S1R-6-07	6	0.31	0.78		0.1	2.2	1000		
FN9222S1R-8-06	8	0.31	0.5		0.1	2.2	1000		
FN9222S-3-06	3	0.31	2.5		0.1	2.2			
FN9222S-3-07	3	0.31	2.5		0.1	2.2			
FN9222S-6-06	6	0.31	0.78		0.1	2.2			
FN9222S-6-07	6	0.31	0.78		0.1	2.2			
FN9222S-8-06	8	0.31	0.5		0.1	2.2			
FN9222SB-10-06	10	0	0.225		0.1		1000		
FN9222SB-10-07	10	0	0.225		0.1		1000		
FN9222SB-1-06	1	0	12		0.1		1000		
FN9222SB-1-07	1	0	12		0.1		1000		
FN9222SB-12-06	12	0	0.11		0.1		1000		
FN9222SB-12-07	12	0	0.11		0.1		1000		
FN9222SB-15-06	15	0	0.075		0.1		1000		
FN9222SB-15-07	15	0	0.075		0.1		1000		
FN9222SB-3-06	3	0	2.5		0.1		1000		
FN9222SB-3-07	3	0	2.5		0.1		1000		
FN9222SB-6-06	6	0	0.78		0.1		1000		
FN9222SB-6-07	6	0	0.78		0.1		1000		
FN9222SR-10-06	10	0.31	0.225		0.1	2.2	1000		

Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance		Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1		Cx1 (μF)	Cy1 (μF)			
FN9222SR-10-07	10	0.31	0.225		0.1	2.2	1000		
FN9222SR-1-06	1	0.31	12		0.1	2.2	1000		
FN9222SR-1-07	1	0.31	12		0.1	2.2	1000		
FN9222SR-12-06	12	0.31	0.11		0.1	2.2	1000		
FN9222SR-12-07	12	0.31	0.11		0.1	2.2	1000		
FN9222SR-15-06	15	0.31	0.075		0.1	2.2	1000		
FN9222SR-15-07	15	0.31	0.075		0.1	2.2	1000		
FN9222SR-3-06	3	0.31	2.5		0.1	2.2	1000		
FN9222SR-3-07	3	0.31	2.5		0.1	2.2	1000		
FN9222SR-6-06	6	0.31	0.78		0.1	2.2	1000		
FN9222SR-6-07	6	0.31	0.78		0.1	2.2	1000		
FN9222SR-8-06	8	0.31	0.5		0.1	2.2	1000		
FN9222U-10-06	10	0.31	0.225		0.1	2.2			
FN9222U-1-06	1	0.31	12		0.1	2.2			
FN9222U-12-06	12	0.31	0.11		0.1	2.2			
FN9222U-15-06	15	0.31	0.075		0.1	2.2			
FN9222U-3-06	3	0.31	2.5		0.1	2.2			
FN9222U-6-06	6	0.31	0.78		0.1	2.2			
FN9222U-8-06	8	0.31	0.5		0.1	2.2			
FN9222UB-15-06	15	0	0.075		0.1		1000		
FN9222UB-3-06	3	0	2.5		0.1		1000		
FN9222UZ-10-06	10	0.31	0.225		0.1	2.2			
FN9222UZ-1-06	1	0.31	12		0.1	2.2			
FN9222UZ-12-06	12	0.31	0.11		0.1	2.2			
FN9222UZ-15-06	15	0.31	0.075		0.1	2.2			

Articles

Article	Rated Current @ambient (A)	Leakage current IEC60939 (A)	Inductance	Capacitance		Resistance (kΩ)	Dist. stock	Read More
			L1	Cx1 (μF)	Cy1 (μF)			
FN9222UZ-3-06	3	0.31	2.5	0.1	2.2			
FN9222UZ-6-06	6	0.31	0.78	0.1	2.2			
FN9222UZ-8-06	8	0.31	0.5	0.1	2.2			

Headquarters, Global Innovation and Development

Switzerland

Schaffner Group

Industrie Nord
Nordstrasse 11e
4542
Luterbach
+41 32 681 66 26
info@schaffner.com

Sales and Application Centers

Finland

Schaffner Oy

Lohjanharjuntie 1109
08500
Lohja
+ 358 50 468 72 84
finlandsales@schaffner.com

France

Schaffner EMC S.A.S.

16-20 Rue Louis Rameau
95875
Bezons
+33 1 34 34 30 60
francesales@schaffner.com

Germany

Schaffner Deutschland GmbH

Ohiostr. 8
76149
Karlsruhe
+49 721 56910
germanysales@schaffner.com

Italy

Schaffner EMC S.r.l.

Via Ticino, 30
20900
Monza (MB)
+39 039 21 41 070
italysales@schaffner.com

Japan

Schaffner EMC K.K.

ISM Sangenjaya 7F
1-32-12 Kamiyama Setagaya-ku
154-0011
Tokyo
+81 3 5712 3650
japansales@schaffner.com

Singapore

Schaffner EMC Pte Ltd.

Blk 3015A Ubi Road 1 #05-09 Kampong Ubi
Industrial Estate
408705
Singapore
+65 63773283
singaporesales@schaffner.com

Sweden

Schaffner EMC AB

Östermalmströg 1
114 42
Stockholm
+46 8 5050 2425
swedensales@schaffner.com

Switzerland

Schaffner EMV AG

Industrie Nord
Nordstrasse 11e
4542
Luterbach
+41 32 681 66 26
switzerlandsales@schaffner.com

India

Schaffner India Pvt. Ltd

Regus World Trade Centre
WTC 22nd Floor Unit No 2238 Brigade
Gateway Campus 26/1 Dr. Rajkumar Road
Mallechwaram (W)
560055
Bangalore
+91 8067935355
indiasales@schaffner.com

United Kingdom

Schaffner Ltd.

Suite 1 Oakmede Place
Terrace Road
RG42 4JF
Binfield
+44 118 9770070
uksales@schaffner.com

United States

Schaffner EMC Inc.

52 Mayfield Avenue
Edison, New Jersey
+1 732 225 9533
usasales@schaffner.com

To find your local partner within Schaffner's global network schaffner.com

© 2024 Schaffner Group The content of this document has been carefully checked and understood. However, neither Schaffner nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG. Latest publications and a complete disclaimer can be downloaded from the Schaffner website. All trademarks recognized.