


Wide input voltage non-isolated and regulated single output



FEATURES

- High efficiency up to 95%
- No-load input current as low as 0.2mA
- Operating ambient temperature range: -40℃ to +85℃
- Negative output available
- Output short-circuit protection
- Pin-out compatible with LM78XX linear regulators

K78Lxx-500R3 series are high efficiency switching regulators and ideal substitutes of LM78xx series three-terminal linear regulators. The converters feature high efficiency, low loss, short circuit protection, positive or negative output voltage, and there is no need for a heat sink. These products are widely used in applications such as industrial control, instrumentation, electric power.

Selection Guide

Certification	Part No.	Input Voltage (VDC)*	Output		Full Load Efficiency (%) Vin Min. / Vin Max.	Capacitive Load (μF) Max.
		Nominal (Range)	Voltage (VDC)	Current (mA) Max.		
EN/IEC	K78L03-500R3	24 (4.75-36)	3.3	500	86/80	680
	K78L05-500R3	24 (6.5-36)	5.0	500	90/84	680
		12 (7-31)	-5.0	-300	80/81	330
	K78L12-500R3	24 (15-36)	12	500	94/91	680
		12 (8-24)	-12	-150	84/85	330
	K78L15-500R3	24 (19-36)	15	500	95/93	680
		12 (8-21)	-15	-150	85/87	330

Note: * For input voltage exceeding 30 VDC, an input electrolytic capacitor of 22μF/50V is required to prevent the module from being damaged by voltage spikes.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
No-load Input Current	Positive output	--	0.2	1.5	mA
Reverse Polarity at Input		Avoid / Not protected			
Input Filter		Capacitance filter			

Output Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Voltage Accuracy	Full load, input voltage range	K78L03-500R3	--	±2	±4	%
		Others	--	±2	±3	
Linear Regulation	Full load, input voltage range		--	±0.2	±0.4	
Load Regulation	Nominal input , 10% -100% load	3.3/±5 VDC output	--	±0.6	--	
		±12/±15 VDC output	--	±0.3	--	
Ripple & Noise*	20MHz bandwidth, nominal input, 10% -100% load		--	20	75	mVp-p
Temperature Coefficient	Operating temperature -40℃ to +85℃		--	--	±0.03	%/℃
Transient Response Deviation	Nominal input, 25% load step change		--	50	250	mV
Transient Recovery Time	Nominal input, 25% load step change		--	0.2	1	ms

Short-circuit Protection	Nominal input	Continuous, self-recovery
Notes: * 1.The "parallel cable" method is used for ripple and noise test, please refer to DC-DC Converter Application Notes for specific information; * 2.With light loads at or below 10%, Ripple & Noise for 3.3V/5V output parts increases to 150mVp-p max., and for 12V/15V output parts to 2%Vo max.		

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Operating Temperature	Derating when operating temperature $\geq 71^{\circ}\text{C}$ (see Fig. 1)	-40	--	85	$^{\circ}\text{C}$
Storage Temperature		-55	--	125	
Pin Soldering Resistance Temperature	Soldering spot is 1.5mm away from case for 10 seconds	--	--	260	
Storage Humidity	Non-condensing	5	--	95	%RH
Switching Frequency	Full load, nominal input	550	--	850	kHz
MTBF	MIL-HDBK-217F@25 $^{\circ}\text{C}$	2000	--	--	k hours

Mechanical Specifications

Dimensions	10.00 x 7.20 x 11.00 mm
Weight	1.0g (Typ.)
Cooling Method	Free air convection

Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032 CLASS B (see Fig. 5-② for recommended circuit)
	RE	CISPR32/EN55032 CLASS B (see Fig. 5-② for recommended circuit)
Immunity	ESD	IEC/EN 61000-4-2 Contact $\pm 4\text{kV}$ perf. Criteria B
	RS	IEC/EN 61000-4-3 10V/m perf. Criteria A
	EFT	IEC/EN 61000-4-4 $\pm 1\text{kV}$ (see Fig. 5-① for recommended circuit) perf. Criteria B
	CS	IEC/EN 61000-4-6 3Vr.m.s perf. Criteria A

Typical Characteristic Curves








Fig. 1



Negative output efficiency Vs input voltage
(full load)



Negative output efficiency Vs output
load (Vin=Vin-nominal)



Design Reference

1. Typical application






Fig. 2 Typical application circuit

Table 1

Part No.	C1/C3 (ceramic capacitor)	C2/C4 (ceramic capacitor)
K78L03-500R3	10μF/50V	22μF/10V
K78L05-500R3		22μF/10V
K78L12-500R3		22μF/25V
K78L15-500R3		22μF/25V



Notes:

1. C1 and C2 (C3 and C4) are required and should be connected close to the pin terminal of the module.
2. Refer to Table 1 for C1 and C2 (C3 and C4) capacitor values. For certain applications, increased values and/or tantalum or low ESR electrolytic capacitors may also be used instead.
3. When using configurations as shown in figure 3, we recommended to add an inductor (LDM) with a value of up to 10μH which helps reducing mutual interference.
4. Converter cannot be used for hot swap and with output in parallel.
5. Connecting a "LC" filter at the converter output helps to further reduced the output ripple. The recommended inductor value (L) is 10μH-47μH.






Fig. 4 External "LC" output filter circuit diagram

2. EMC compliance circuit




FUSE	MOV	LDM1	C0	C1/C2	C5	LDM2
Selected fuse value according to actual input current	S20K30	82μH	680μF /50V	Refer to table 1	4.7μF /50V	12μH

Note: For EMC tests we use Part ① in Fig. 5 for immunity and part ② for emissions test. Selecting based on needs.

3. For additional information please refer to DC-DC converter application notes on www.mornsun-power.com

Dimensions and Recommended Layout

THIRD ANGLE PROJECTION 



Note:
Unit: mm[inch]
Pin section tolerances: $\pm 0.10[\pm 0.004]$
General tolerances: $\pm 0.50[\pm 0.020]$

Pin-Out		
Pin	Positive Output	Negative Output
1	Vin	Vin
2	GND	-Vo
3	+Vo	GND

Notes:

1. For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58210080;
2. The maximum capacitive load offered were tested at nominal input voltage and full load;
3. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity<75%RH with nominal input voltage and rated output load;
4. All index testing methods in this datasheet are based on our company corporate standards;
5. We can provide product customization service, please contact our technicians directly for specific information;
6. Products are related to laws and regulations: see "Features" and "EMC";
7. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

MORNSUN Guangzhou Science & Technology Co., Ltd.

Address: No. 8 Nanyun 4th Road, Huangpu District, Guangzhou, China

Tel: 86-20-38601850

Fax: 86-20-38601272

E-mail: info@mornsun.cn

www.mornsun-power.com